






Specification:


Material:
 Contact Material: Brass
 Contact plating: Au or Sn Over 50μ" Ni
 Insulator Material: Black Polyester UL94V-0
 Standard: LCP+30%G.F

Electrical:
 Current rating: 1.0Amps/contact max.
 Contact resistance: ≤20mΩ/contact
 Insulation resistance: ≥1000MΩ at V=100V
 Withstanding Voltage: 550V AC/minute

Mechanical:
 Mechanical life cycle: min.200
 Operating temperatures: -45°C to +105°C
 Soldering temperature: 260°C, 5s.



Recommended P.C.B
 Layout(±0.05)



Ordering Information

EH127110DS - 2XX X X X 01

- No. of pins
2*3-2*32
- Plating Option
A = Gold Flash
B = 3U" Gold
C = 5U" Gold
E = 15U" Gold
T = Tin
Z = Special
- Insulator Material
Option
A = PBT
B = PA6T
F = LCP
Z = Special
- Packing Option
A = Tray
B = Bag
C = Tube
Z = Special

Fortune Star		Fortune Star Technical Co., Limited	
TITLE: 1.27mm Ejector Header Dual row Dip type			
TOLERANCES UNLESS OTHERWISE SPECIFIED:	DRAWN	Robert	DATE: 2012-03-28
X.XX ±0.25	CHECKED	Jhon	PROJECTION
X.X ±0.35	APPROVED	Jack	SCALE: 1:1
X. ±0.50			UNIT: MM
X.X° ±2°			SHEET: 1/1
X.° ±3°			REV: A